

THE STRONGEST IN ITS CLASS!

HOLDER

NEW HOLDER S-SERIES

HOLDER S 100 | HOLDER S 115 | HOLDER S 130









VARIOUS APPLICATIONS:

WINTER MAINTENANCE

- Snow ploughing, blowing, sweeping, loading
- Cross-country ski-tracks
- Spreaders
- Drine spraying
- Ice scraping

MOWING AND GROUND CARE

- Mowing-suction combination
- Verge mowing
- Mowing (with rotary, wide area, cylinder and reach arm mower)
- Mulching
- Hedge cutting
- Watering

SWEEPING AND CLEANING

- Sweeper-suction combination
- Sweeping brush
- Removal and cleansing of road markings
- Cleansing of reflection posts and traffic signs
- Rubber removal
- Leaf removal
- Washing
- Synthetic turf cleaner
- Weed control (i.e. hot water)

TECHNICAL DATA

ENGINE	Deutz 4-cylinder 4-stroke turbo diesel , Tier-4-final, Stage-5-ready
Displacement	3621 cm ³
Power	74,4 kW (102 HP) / 85 kW (115 HP) / 95 kW (128 HP)
Torque	410 Nm
Rated speed	2200 rpm
Cooling	Water cooling
Fuel tank capacity	82
DRIVE	Hydrostatic traction drive, controlled digital-electrically, stepless road speed control, Dual Drive, permanent four-wheel drive, four wheels of the same size
Maximum speed	40 km/h
Brakes	Hydraulically actuated wet disc brake, acts on all four wheels as four-wheel brake, electric stop brake acts on both axles
HYDRAULICS	Hydraulic pump 42 l/min or on request tandem pump with adjustable flow divider 40 l/min + 25 l/min, variable displacement pump 0-120 l/min
Hydraulic oil quantity	30
Lifting capacity	Front 2700 kg , CAT II, 3-dimensionally movable
Control valves	Up to 4 double-acting front valves and up to 3 double-acting rear valves
WEIGHT	Including driver at 75 kg, depending on tyres and equipment
Tare weight	approx. 3100 - 3450 kg
Permissible gross weight	5500 kg / optionally: 6000 kg
Permissible axle load	Front 3200 kg / rear 3200 kg
Tow-bar load on the trailer coupling	Max. 800 kg
Towing capacity	Unbraked 2500 kg / overrun braked 4500 kg
Maximum payload	2400 kg / optionally: 2900 kg
DIMENSIONS	Depending on tyres
Wheelbase	1827 mm
Total length	3920 mm
Total height with cab	2233 - 2295 mm
Total outside width	1330 - 1580 mm
Turning circle inside /outside	1974 mm / 3045 mm

HOLDER IN ACTION: www.youtube.com/user/maxholdergmbh



YOUR TOP ADVANTAGES

- High working hydraulic: simultaneous operation of two proportional functions, free set up of Joystick, 3 independent drives for attachments
- Mechanical front PTO and wheel stabilizer
- Improved agility (outer turning radius of 3045 mm)
- Three different seating options: one seat, two seats or one adjustable seat
- Touch display and LED lightning



NO COMPROMISES