OPTIONAL ACCESSORIES FOR TECHNICAL SEARCH EQUIPMENT

FOR LEADER CAM / LEADER SEARCH / LEADER HASTY / LEADER SCAN CONTROL BOXES

BATTERY ALONE (each)	
Ref	D11.04.341
Туре	Lithium ion. 37 Wh
Weight	300 g

Charger dimensions	H 10.5 x D 4.5 x L 3.5 cm
Charger weight	200 g
Charger input voltage	100 - 240 VAC / 50-60 Hz
International connection adaptors	UK, EU, AUS, USA



SPARE BATTERY PACK		
Ref	200 61 55	
Weight with 10 batteries (not supplied)	300 g	

NOISE-REDUCING HEADPHON	NES	
Ref 1 pair headphones only	200 63 82	
OPTIONAL 2ND SET NOISE-REDUCING HEADPHONES		
1 pair headphones supplied with Y connector for connecting 2 pairs headphones to control box simultaneously	D11.04.340	



Ref	200 63 03
Material	Braided fabric supplied with fixing clasps
Length	120 cm



ACCESSORIES SPECIFICALLY FOR SEISMIC SENSOR



SPIKES (each)		
Ref	200 31 13	
Function	Allows sensor to be used on soft ground	
Material	Steel	
Water at 1		

MAGNETS (each)	
Ref	200 35 14
Function	Allows sensor to be used on metal debris
Material	Steel
FO	

COMMUNICATION PROBE		
Ref	D11.04.337	
Microphone/loudspeaker	Yes	
Material	stainless steel	
Diameter	38 mm	
Ingress protection	IP67	
Response frequency	300 Hz to 3500 Hz	
Cable length	8 m	
Cable type	Orange anti-abrasion cable	
O. C.		

ACCESSORIES SPECIFICALLY FOR SEARCH CAMERA



WATER-RESISTANT PLUGS		
Ref	200 38 45	
Function	Makes camera unit watertight up to 2m deep	
Material	Plastic + rubber seal	

25 m cable	D11.04.356
90 m cable on reel	D11.04.348
Connectors	Metal
Cable type	Orange anti-abrasion cable



Water-resistant camera (non-articulating) to 90 m depth with 90 m of cable on reel	D11.04.347
Reel of additional 90 m of cable	D11.04.348

