



## ELECTRIC FAN SA 315

### Extractor/Blower electric fan

#### For safe removal of dangerous gases:

- Ventilation by blowing or extraction
- With 300mm diam. ZAG couplings for connection to suction and blowing ducts
- Stainless steel body.

**Compact**, stows easily in the trunk of a vehicle.

**Portable, easy to handle, stable and robust**

### Characteristics

Model	SA315
Reference	I63.00.022
Nominal air flow	2 560 m <sup>3</sup> /h
Open air flow	9000 m <sup>3</sup> /h
Weight	29,8 kg
Dimensions L x H x D	374 x 435 x 460 mm
Outlet grille diameter	300 mm
Engine	1.1 kW IP55 protection
Power supply	Single phase - 230V – 50Hz
Electrical safety	Meets EN 50178 for user safety (leakage current less than 3.5 mA)
Power consumption in steady operation	6.1 A
Mains plug	CE male plug – 220 V
Noise level	77 dB at 3 m
Ventilation type	Blowing and Extraction
Application	Smoke or gas removal from premises. Smoke removal from basements and ships

#### Optional accessories:

Extraction/blowing duct for SA315. Ø 300 mm - L 5m

I61.20.002

Ventilation tactics in the catalogue or at [www.leader-group.eu](http://www.leader-group.eu)  
 Freely downloadable interactive ventilation courses at [www.leader-educexpert.com](http://www.leader-educexpert.com)  
 As part of our policy of constant research to improve our products, we reserve the right to modify our products' characteristics at any time without notice